

ENEOS CITY Performance 10W-40

High Performance 4T SCOOTER Engine Oil

High performance oil specifically designed for scooters, maxi-scooters, 3-wheelers and motorcycles with "dry type" clutch system and fitted with 4 stroke engines, with or without catalytic converters. Formulated for all scooters for city-ride conditions and reinforced with a synthetic base oil stock to provide outstanding protection during extreme conditions, cold start, short and long city-rides, high temperatures and engine idling at traffic lights and in traffic jams. Specification of this oil and viscosity grade meets the recent recommendations from Japanese as well as European motorcycle manufacturers. This oil is engineered to keep engine clean from deposits and oil consumption low.

PERFORMANCE STANDARDS

API SJ

JASO MB

Designed to provide low friction coefficient meeting JASO MB standard.

Engineered for OEM performance in Japanese Motorbikes.

APPLICABLE MOTORBIKES

Designed specifically for modern 4 Stroke automatic transmission engines in scooters, maxi-scooters, 3-wheelers and motorcycles with "dry type" clutch system, with or without catalytic converters.

Strictly not to be used in wet clutch motorcycle engines

CONTAINERS

1L, 4L, 60L.

TYPICAL PROPERTIES

SAE viscosity grade	10W-40
Density (15 °C), g/cm ³	0.87
Flash point (COC), °C	225
Kinematic viscosity (40 °C), mm ² /s	94.4
(100 °C), mm ² /s	14.2
Viscosity index	154
Pour point, °C	-37.5
TBN (HClO ₄), mg KOH/g	6.5
TAN, mgKOH/g	2.1
HTHS (150 °C), mPa.s	4.0

Note: The typical properties may be changed without notice. (April 2020)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.