



ENEOS Premium Hyper R1 5W30

Fully-Synthetic long-life motor oil

ENEOS Premium Hyper R1 5W30 is high performance fully-synthetic motor oil engineered especially for most modern engine from Renault. This is very low ash engine oil designed for long life and top efficiency of exhaust gas recirculation systems.

Emissions of harmful gas have been halved in the last five years thanks to research by carmakers. A major actor in this research, Renault is continuing its work on improving the emission levels of cars, which they manufacture. One of the main thrusts of this policy is gradually equipping range vehicles with new technologies, with requirement to use new technology, low emission engine oil. The objective is to increase performance while cutting fuel consumption and emissions.

● SPECIAL FEATURES

1. Fully-Synthetic Motor Oil with Deposit control Formula

This high-performance very low ash engine oil has been engineered for protecting maximum life and providing maximum efficiency of the exhaust emission reduction systems used in both gasoline and diesel engine vehicles. This is very stable, stay-in-grade oil intended for use as catalyst compatible oil in vehicles with Diesel Particulate Filter and Three Way Catalyst in high performance car and light commercial vehicles engines requiring low SAPS oil. These oils will increase the DPF and TWC life. Especially recommended use in cars equipped with modern engines from Renault.

2. Longer Drain Intervals

Ensures exceptional engine durability and allows the extra long oil drain intervals as recommended by Renault, thanks to its exceptional oxidation resistance.

3. Excellent characteristics in all operation Conditions

Allows extended operation at extremely high temperatures due to formulation which prevents oils from oxidative thickening and breakdown. At low temperatures this oil provides excellent fluidity allowing easy cold-start and quick oil circulation inside the engine.

● PERFORMANCE LEVELS

- ACEA C4 (10)
- RENAULT RN0720
- MERCEDES-BENZ: MB 226.51

● APPLICABLE VEHICLES

Gasoline and Diesel engines in passenger cars and light duty commercial vehicles requiring very low ash C4 specification oil.

Designed especially for Renault engines requiring manufacturer specification RN0720 engine oil.

● CONTAINERS

1L, 4L, 20L, 200L and 1000L IBC

● TYPICAL PROPERTIES

SAE viscosity grade	5W-30
Density (20°C), g/cm ³	0.850
Flash point (COC), °C	200
Kinematic viscosity (40°C), mm ² /s	68.0
(100°C), mm ² /s	11.7
Viscosity index	164
Pour point, °C	-39.0

Note: The typical properties may be changed without notice. (February 2013)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.