



# ENEOS SUSTINA 5W-30 SN/RC

## FULLY SYNTHETIC PREMIUM MOTOR OIL

**MATERIAL CODE: EMA1002**

ENEOS SUSTINA 5W-30 SN/RC is the Ultimate Performance Fully Synthetic, Ultra Wide Range Motor Oil. JX has developed 'Pro-racing' grade with Zero-weight technology and using JX Nippon Oil & Energy's own W BASE and ZP technology to maintain an extremely stable oil viscosity over a wide temperature range. ENEOS SUSTINA 5W-30 SN/RC is the Ultra-modern Fully –synthetic Motor Oil for Gasoline specially formulated to meet the latest ILSAC GF-5 specification which is an improvement in engine oil performance compared to the current GF-4 Specification. The new ENEOS SUSTINA 5W-30 SN/RC GF-5 Oil provides better fuel economy, increased emission system durability enhanced piston cleanliness, reduced engine sludge, and improved turbocharger protection.

### SPECIAL FEATURES

**1. Outstanding oxidation Stability at High temperatures.**

ENEOS SUSTINA 5W-30 meets the latest API SN standard for gasoline oils.

**2. Excellent Engine Cleanliness and Water Resistance.**

ENEOS SUSTINA 5W-30 SN/RC' s excellent engine cleanliness and wear resistance have been proven in official laboratory tests in the United States. This performance has also been confirmed in the fill range of vehicle tests.

**3. Little Oil consumption**

The consumption of motor oils depends largely on the type of base oil. Because ENEOS SUSTINA 5W-30 SN/RC motor oil is blended from high performance Oils, it has little Oil consumption, so users can look forward to adding less Oil to their engines.

**4. Meets Latest API Standard**

The outstanding performance of ENEOS SUSTINA 5W-30 SN/RC is proven by its certification for the SN Specification, the latest Motor Oil standard issued by the American Petroleum Institute.

### PERFORMANCE LEVEL

API SN/RC  
 ILSAC GF-5

### APPLICATIONS.

Motor Oil for Gasoline Engines.  
 Sports cars with large displacements and high outputs, high-performance passenger cars, racing-specification cars, etc.

### TYPICAL PROPERTIES.

SAE Viscosity Grade	5W-30
Quality Grade	SN /RC
Appearance	Brown
Density (15°C), g/cm <sup>3</sup>	0.847
Flash Point (COC), °C	234
Kinematic Viscosity (40°C), mm <sup>2</sup> /s	51.76
(100°C), mm <sup>2</sup> /s	10.32
Viscosity Index	193
Pour Point, °C	-50
TAN, mg KOH/g	1.86
TBN (HCL), mg KOH/g	6.96
Colour (ASTM)	L 4.5

### PACK SIZE

1L, 4L

Note: The Typical Properties may be changed without notice.



## Handling Precautions

▼ Follow these precautions when handling this product.

<b>! CAUTION</b>  <b>Handling Precautions</b>	<ul style="list-style-type: none"><li>● <u>Inflammation can occur if oil enters the eyes.</u> When handling this oil, wear <u>protective goggles</u> or take other measures to <u>prevent eye contact</u>.</li><li>● <u>Inflammation can occur if oil comes into contact with skin.</u> When handling this oil, wear <u>protective gloves</u> or take other measures to <u>prevent skin contact</u>.</li><li>● Do not drink this oil. (Swallowing this oil can cause diarrhea and nausea.)</li><li>● <u>Keep out of reach of children.</u></li><li>● Read the Material Safety Data Sheet (MSDS) for this product before using the product. Obtain the Material Safety Data Sheet from where you purchased the product.</li></ul>
<b>First Aid</b>	<ul style="list-style-type: none"><li>● In case of eye contact, rinse eyes thoroughly with clean water and consult with a physician.</li><li>● In case of skin contact, wash skin thoroughly with soap and water.</li><li>● If this oil is swallowed, do not induce vomiting. Consult with a physician immediately.</li></ul>
<b>Disposal of Used Oil and Containers</b>	<ul style="list-style-type: none"><li>● Do not apply pressure to empty containers. The containers may burst if pressure is applied.</li><li>● Do not weld, heat, drill, or cut the containers. The remaining oil may ignite and the containers may explode.</li><li>● Follow all applicable laws and regulations when disposing of used oil or containers. If you are unsure of the proper disposal methods, consult first with the seller of the oil.</li></ul>
<b>Storage Method</b>	Seal the container tightly after use in order to prevent dirt, moisture, etc., from entering the oil. Store in a dark location. Avoid direct sunlight.